

Legrand cabling system LCS³ fibre optic

cables (continued)



0 325 13



0 325 10



0 325 08

Technical characteristics **see e-catalogue**

LSOH sheath (except Cat.Nos 0 325 13, 0 325 15, 0 325 23, 0 325 24, 0 325 25, 0 325 40, 0 325 41 and 0 325 42)

Euroclass D_{ca} (except Cat.Nos 0 325 05/07/13/15/23/24/25/40/41/42)

Colour code: FOTAG

Compliance with the EN 50173-2, ISO IEC 11801 standards

Packing on drum (2000 m)

Tight structure: "easy strip"

Pack	Cat.Nos		OS 2 single-mode fibre optic cables (9/125 µm) - (OS1 compatible) For single-mode installations 9/125 µm, type OS 2 Yellow or black sheaths for outdoor, rodent guard... Indoor/outdoor (glass strands)
	Loose tube	Tight structure 900 µm	
2000	0 325 02		4 fibres
2000	0 325 03		8 fibres
2000	0 325 23		Outdoor, corrugated steel tape 4 fibres
2000	0 325 24		Outdoor, corrugated steel tape 8 fibres
2000	0 325 25		Outdoor, corrugated steel tape 24 fibres
2000	0 325 12		Indoor/outdoor (glass strands) 6 fibres
2000	0 325 13		Outdoor, corrugated steel tape 6 fibres
2000	0 325 14	0 325 50	Indoor/outdoor (glass strands) 12 fibres
2000	0 325 15		Outdoor, corrugated steel tape 12 fibres
2000	0 325 51		Indoor/outdoor (glass strands) 24 fibres

Pack	Cat.Nos		OM 3 multimode fibre optic cables (50/125 µm) "Bend insensitive" For multimode installations 50/125 µm, type OM 3 Aqua sheaths Suitable for 10 Giga Ethernet networks Indoor/outdoor (glass strands)
	Loose tube	Tight structure 900 µm	
2000		0 325 10	6 fibres
2000		0 325 11	Indoor/outdoor (glass strands) 12 fibres
2000	0 325 53	0 325 52	Indoor/outdoor (glass strands) 24 fibres
2000	0 325 37		Indoor/outdoor (glass strands) 4 fibres
2000	0 325 38		Indoor/outdoor (glass strands) 8 fibres
2000	0 325 39		Indoor/outdoor (glass strands) 12 fibres
2000	0 325 40		Outdoor, corrugated steel tape 8 fibres
2000	0 325 41		Outdoor, corrugated steel tape 12 fibres
2000	0 325 42		Outdoor, corrugated steel tape 24 fibres

Pack	Cat.Nos		OM 2 multimode fibre optic cables (50/125 µm) For 50/125 µm multimode installations (OM 2) Orange jacket or black for outdoor, corrugated
	Loose tube	900 µm Tight buffer	
2000		0 325 55	Indoor/outdoor (universal) 4 fibres
2000	0 325 04	0 325 08	Indoor/outdoor (universal) 6 fibres
2000	0 325 05		Outdoor, corrugated steel tape 6 fibres
2000	0 325 06	0 325 09	Indoor/outdoor (universal) 12 fibres
2000	0 325 07		Outdoor, corrugated steel tape 12 fibres