

# Mosaic™ Programme mechanisms

## dimming control



Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	Dimmer switches 110-230 V~ - 50 Hz
1	2 modules 0 784 07	<p>Can be remotely controlled via non-illuminated pushbuttons (p. 877), with each pushbutton able to perform the dimming function When switched on, lightens at the level set before last switched off For installation in flush-mounting box depth 40 mm min</p> <p><b>Universal dimmer without neutral, 2-wire</b> For all types of lamps: - dimmable LEDs: 5 W to 75 W (10 lamps max.) - dimmable compact fluorescent lamps: 5 W to 75 W (10 lamps max.) - halogen with ferromagnetic or electronic transformer: 3 VA to 400 VA - fluorescent tube - ballast: 3 VA to 200 VA - halogen and incandescent 230 V: 3 W to 400 W When switched on, gradually (2 seconds) lights up at the level set before last switch-off Functioning: - dimming mode - pre-set level mode (0%, 33%, 66%, 100%) - nightlight mode: dimming down of the lamp for 1 hour</p> <p>○ White ● Alu</p>
1	0 792 07	
1	0 784 05	<p><b>Leading edge dimmer, without neutral</b> For the following types of lamps: - halogen 230 V and incandescent: 40 W to 600 W - halogen with ferromagnetic or electronic type L transformer: 40 VA to 600 VA</p> <p>○ White</p>
1	5 modules 0 784 02	<p><b>1000 W dimmer, with neutral</b> For the following types of lamps: - halogen with ferromagnetic or electronic transformer: 100 VA to 1000 VA - halogen and incandescent 230 V: 100 W to 1000 W When switched on, gradually (2 seconds) lights up at the level set before last switch-off 5 LEDs displaying the current level of the circuit</p> <p>○ White</p>

Pack	Cat.Nos	Dimmer switch with neutral, for 0-10 V ballast
1	2 modules 0 784 04	<p>For lamps with 0-10 V ballast, 600 VA</p> <p>○ White</p>
1	2 modules 0 784 10	<p><b>Auxiliary control unit for DIN dimmer</b> Remote control dimming peripheral for local control of a remote control dimmer, with the same easy operation as a conventional dimmer A power supply Cat.No 0 036 80 is required for controlling DIN-rail modular remote control dimmers Cat.Nos 0 036 60/71 (p. 94)</p>