

## Mosaic™ Programme mechanisms

### rear pluggable RJ 45 sockets and switches



0 786 22




0 786 26



0 779 00

Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	Rear pluggable RJ 45 sockets
10 10	0 786 28 0 786 29	<p>For use with area distribution boxes system Connection to boxes via RJ 45-RJ 45 cords Used to create Cat. 6<sub>A</sub>, 6 and 5e links in accordance with standards ISO 11801 ed.2.0, EN 50173-1 and EIA/TIA 568 B2 Multi-directional cable entry Can be installed in all supports minimum depth 40 mm. 2 modules</p> <p><b>Cat. 6<sub>A</sub> STP</b>  <input type="radio"/> White  <input type="radio"/> Alu</p>
10 10	0 786 23 0 786 27	<p><b>Cat. 6 FTP</b> 9 contacts  <input type="radio"/> White  <input type="radio"/> Alu</p>
10 10	0 786 22 0 786 26	<p><b>Cat. 6 UTP</b> 8 contacts  <input type="radio"/> White  <input type="radio"/> Alu</p>
10 10	0 786 21 0 786 25	<p><b>Cat. 5e FTP</b> 9 contacts  <input type="radio"/> White  <input type="radio"/> Alu</p>
10 10	0 786 20 0 786 24	<p><b>Cat. 5e UTP</b> 8 contacts  <input type="radio"/> White  <input type="radio"/> Alu</p>
1 1	0 779 00 0 779 01	<p><b>Flush-mounting switches</b>            Non manageable switches            For networking computer peripherals without a patch panel: computers, printers, servers, etc.            Possibility of extending an existing network by simply replacing an RJ 45 socket            Tool-free connection            Conform with standards IEEE 802.3 (Ethernet) and EN 500 81/82-2 (EMC requirements)            Installation in all supports with minimum 40 mm depth            6 ports at the front + 1 side RJ 45 connector for cabling and carrying out link tests            Port status display integrated into the RJ 45 connectors            Labelling of each port from 1 to 6 and marker holder for switch identification            6 modules</p> <p>230 V supply PoE supply (802.3 ag)</p>



## Mosaic™ Programme mechanisms

### data sockets



0 765 35



0 786 13



0 786 17

Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	RJ 45 doubler sockets
10 10	0 765 39 0 765 38	<p>1 module <b>Ethernet/Ethernet</b>            FTP - 9 contacts            UTP - 8 contacts</p>
10 10	0 765 37 0 765 36	<p><b>Telephone/Ethernet</b>            FTP - 9 contacts            UTP - 8 contacts</p>
10	0 765 35	<p><b>Telephone/telephone</b> 45 contacts</p>
10 10 10 10 10	0 786 04 0 786 10 0 786 13 0 786 02 0 786 03 0 786 09	<p><b>Adaptors for RJ 45 connector</b>            Equipped with transparent marker holder            White - 2 modules</p> <p>For single Keystone connector</p> <p>For 2 Keystone connectors</p> <p>For 2 Keystone connectors - inclined 45°</p> <p>For single Systemax connector</p> <p>For double Systemax connector</p> <p>For single Infra+ connector</p>
1 1 1 1	0 786 14 0 786 16 0 786 17 0 786 18	<p><b>Optical sockets - 2 modules</b>            For connecting 2 fibres to the workstation            Equipped with 1 duplex adaptor            Supplied with protective caps</p> <p>SC/APC single mode fiber optic socket</p> <p>Socket with 2 ST optical adaptors bayonet connection</p> <p>Socket with 2 SC optical adaptors push-pull connection</p> <p>Socket with 2 LC optical adaptors push-pull connection</p>

SUB D, USB data sockets and USB extender, **p. 896-897**

