

# Mosaic™ Programme mechanisms

## audio and video sockets (continued)



Pack	Cat.Nos		Pack	Cat.Nos	
1	0 787 99	<b>Videoprojector switch</b> Universal remote switch allowing to turn ON or place in STANDBY mode a video projector Works with all videoprojectors or TV through IR learning process Installed close to the room's lighting switches, it replaces the constructors remote and fosters the ignition and extinction of the video projector therefore reducing energy consumption and extending the bulb's lifetime ○ White	1	0 787 55 0 792 55	<b>3-pole XLR sockets</b> Provide the stereo link for microphone, amplifier, mixing console, etc. Recommended cable: 1 audio pair 0.14 mm <sup>2</sup> to 0.5 mm <sup>2</sup> shielded Max. cable length: 50 m (without amplifier) 2 modules ○ White - fast screw connection female ● Alu - fast screw connection female
1	0 787 79	<b>Jack sockets 3.5 mm</b> 3.5 mm Jack connectors can be used to create audio/video links <b>Preterminated sockets - 1 module</b> Equipped with cord, length 15 cm ○ White ● Alu	1	0 787 60	<b>4-pole Speakon</b> Used to connect power enclosures Recommended cable: 2 audio pairs 4 mm <sup>2</sup> Max. cable length: 50 m (without amplifier) 2 modules ○ White - fast screw connection female
1	0 787 64 0 792 64	<b>4 screw-type female 3.5 mm Jack socket - 1 module</b> ○ White ● Alu	10	0 787 51 <sup>1</sup>	<b>Loudspeaker sockets</b> Terminal 4 mm <sup>2</sup> ○ White - 2 modules
1	0 787 73	<b>Solder-type female 3.5 mm Jack socket - 1 module</b> ○ White	10	0 787 50 0 792 50	○ White - 1 module ● Alu - 1 module
1	0 787 47	<b>Female 2 RCA sockets</b> Provide the stereo audio link for any peripheral device such as a DVD drive, camera, video recorder 1 module <b>Preterminated</b> Equipped with a 15 cm cord ○ White	1	0 787 76	<b>Attenuator</b> 100 V - 25 W Allows to adjust power to 25 W from a balanced 100 V loudspeaker line 2 modules ○ White
1	0 787 53	<b>Connection via screw terminals</b> ○ White	1	0 787 58	<b>Other audio and video sockets</b> <b>Female BNC 75 socket - 1 module</b> Provides the composite video link for any peripheral device such as a DVD drive, camera, video recorder, etc ○ White
1	0 787 54 0 792 54	<b>Female 3 RCA sockets</b> Provide the composite video and stereo audio links for any peripheral device such as a DVD drive, camera, video recorder, videoconferencing, etc Connection via screw terminals 1 module ○ White ● Alu			

1: Can be installed in receptacles for floor sockets (p. 479)